



SPE-150/WS

Order No.: 10.1620

EUR 22,90

RRP *

PRODUCTINFOS

Flush-mount full range speakers, 15 W

- Dual cone
- Slimline design with fixed metal grille
- Suitable for mounting into ceilings, walls and car doors

TECHNICAL SPECIFICATIONS

Impedance (Z)	4 Ω
Operating voltage	-
Frequency range	100-12,000 Hz
Resonant frequency (fs)	-
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	-
Power rating	-

Peak music power output	30 W
Sensitivity	89 dB/W/m
Max. rated SPL	-
Max. voltage	-
Radiation angle, horizontal	
Radiation angle, vertical	
Suspension compl. (Cms)	-
Moving mass (Mms)	-
Mech. Q factor (Qms)	-
Electr. Q factor (Qes)	-
Total Q factor (Qts)	-
Equivalent volume (Vas)	-
DC resistance (Re)	-
Force factor (BxL)	-
Voice coil induct. (Le)	-
Voice coil diameter	-
Voice coil former	-
Linear excursion (X_{MAX})	-
Eff. cone area (Sd)	-
Magnet weight	-
Magnet diameter	-
Mounting cutout	Ø 120 mm
Mounting depth	34 mm
Mounting hole diameter	-
Hole spacing X-axis	-
Hole spacing Y-axis	-
Dimensions	Ø 153 mm x 45 mm
Outside diameter	-
Width	-
Height	-
Depth	-
Protective class	
Admiss. ambient temp.	-
Weight	500 g
Sales unit	-
Type of speaker	130

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.