

128380 USB4 Cable, USB-C Male to USB-C Male, 0.5m, 40Gbps, PD 3.1 240W, 8K/60Hz, Thunderbolt 3/4 Compatible, Black

Product Images





USB 4 40 Gbps

USB 4 20 Gbps

USB3.1 10 Gbps

USB3.0 5 Gbps

USB2.0 480 Mbps

40GB/s **240W**

240W Charging
Support PD 3.1 Fast Charging



40Gbps Superspeed Sync
Stable signal with no delay




8K/60Hz

8K@60Hz UHD Video Output



USB-C to C

Mirror Mode



Extend Mode





Short Description

- **Connector:** USB-C Male to USB-C Male (Thunderbolt 3/4 compatible)
- **USB standard:** USB4
- **Data transfer rate:** Up to 40Gbps
- **Power Delivery:** PD 3.1 up to 240W (48V/5A), E-marker chipset
- **Video support:** Up to 8K@60Hz, DP Alt Mode
- **Display protocols:** DisplayPort 1.4a, PCIe 3.0
- **HDR / HDCP:** HDR10, HDCP 1.4 / 2.3
- **Compatibility:** USB4, Thunderbolt 3/4, USB 3.2, USB 2.0
- **Shielding:** Double shielding
- **Jacket:** Premium braided cotton mesh
- **Housing:** Aluminum casing
- **Length:** 0.5m
- **Color:** Black

Description

The 128380 USB4 C to C cable is engineered for ultra-high-speed data transfer, advanced display output, and high-power charging through a single USB-C connection.

Built on USB4 technology, it supports data transfer speeds of up to 40Gbps and is compatible with Thunderbolt 3 and Thunderbolt 4 devices. The cable enables seamless connectivity between laptops, tablets, smartphones, external SSDs, docks, and high-resolution displays, with video output support up to 8K at 60Hz via DisplayPort 1.4a and DP Alt Mode.

Equipped with an integrated E-marker chipset and Power Delivery 3.1 support, the cable delivers up to 240W (48V/5A), making it suitable for power-hungry laptops and professional devices. Premium braided cotton mesh, double shielding, and an aluminum housing ensure stable performance, signal integrity, and long-term durability.

Additional Information

Angled Plug.	No
Shielded.	Yes
Connector 1.	USB-C, male
Connector 2.	USB-C, male
Approval and Compliance.	ROHS, REACH
Package Contents.	USB 4 C to C Cable, 0.5m
Color.	Black
Model Number.	128380
Cable Length.	0.5m
Dimensions (W x D x H).	4.8 x 4.8 x 500 mm
Product weight (kg).	0.035
USB Power Delivery (PD).	240W
Conductor material.	Copper
Data Rate.	40Gbps
Cable Jacket material.	PVC
Standards.	USB 4 Gen 3x2

