



Watering clock WT 2

3-way distributor incl. watering clock. The watering stops automatically once the selected time has lapsed (max. 120 minutes). With G1 tap connector and G3/4 reduction piece.

1 2 independent, adjustable water connections and 1 outlet with water timer

- Ideal for connecting three hoses to a single tap with G1 thread

3 Plastic thread

- Simple attachment to the tap

2 Smooth-running union joint

- Simple attachment to the tap

4 Includes tap adaptor and pre-filter

- For fast connection with the garden hose



Watering clock WT 2

- Smooth-running union joint
- Plastic thread for attachment to the tap
- Includes tap adaptor and pre-filter
- Watering up to 120 min
- Watering stops on expiry of a preset time

Technical data

Order no.	2.645-209.0	
EAN code	4039784620278	
Weight	kg	0.4
Dimensions (L × W × H)	mm	92 × 225 × 200
--	When connecting these products to the drinking water network, you must observe the requirements of EN 1717. If necessary, ask your sanitary specialist.	

ACCESSORIES FOR WATERING CLOCK WT 2

2.645-209.0

KÄRCHER



		Order no.					Price	Description	
Kärcher Rain System®									
Kärcher Rain Box	1	2.645-238.0						The extendable Kärcher Rain Box with filter, drip collars, connection parts and hoses is the ideal ready-for-connection starter set for efficient garden watering.	☐
Sprinklers									
Oscillating sprinkler OS 3.220	2	2.645-133.0						Oscillating sprinkler OS 3.220 for watering medium-sized and large areas and gardens. Infinite coverage adjustment. Extremely durable gear drive. Maximum coverage: 220 m2	☐
Hose connection systems									
Universal Hose Connector with Aqua Stop	3	2.645-192.0						Universal hose coupling with Aqua Stop. Ergonomic design for convenient handling.	☐
Universal Hose Connector	4	2.645-191.0						Ergonomically designed universal hose coupling for convenient handling.	☐
Hoses									
PrimoFlex® hose - 1/2" 20 m	5	2.645-138.0						The PrimoFlex® (1/2") flexible garden hose is 20 m long, temperature-resistant, comes with pressure-resistant reinforcement technology and contains no substances that are harmful to health. Bursting pressure: 24 bar.	☐

☐ Available accessories.