




Cooler Master's high-performance series of CPU air coolers, the Hyper series, is back with the Hyper 411 Nano. The Hyper 411 Nano brings a crop of excellent features to round out the already cutting-edge performance of the Hyper series. With direct contact technology for ultra-rapid heat transfer, an all-black aesthetic, wide-ranging compatibility with both AMD and Intel CPUs, and an easy-to-use fan mount system, the Hyper 411 Nano is an ice-cold beast.

# HYPER 411 NANO




## DIRECT CONTACT TECHNOLOGY

4 heat pipes with direct contact ensure efficient and rapid heat transfer



## ALL BLACK AESTHETIC

A new all black aesthetic gives the Hyper N a modern, sleek look



## AMD AND INTEL COMPATIBILITY

Improved mounting ensures compatibility with the latest AMD and Intel CPU sockets



## EASY FAN MOUNT

Easily mount fans using a set of provided clips

**DIRECT CONTACT TECHNOLOGY** - 4 heat pipes with direct contact ensure efficient and rapid heat transfer

**ALL BLACK AESTHETIC** - A new all black aesthetic gives the Hyper N a modern, sleek look

**AMD AND INTEL COMPATIBILITY** - Improved mounting ensures compatibility with the latest AMD and Intel CPU sockets

**EASY FAN MOUNT** - Easily mount fans using a set of provided clips

## SPECIFICATIONS

|                        |                                                                   |                                               |
|------------------------|-------------------------------------------------------------------|-----------------------------------------------|
| Product Name           |                                                                   | Hyper 411 Nano                                |
| Product Number         |                                                                   | RR-H410-25PK-R1                               |
| Exterior Color         |                                                                   | Black                                         |
| CPU Socket             | Intel® LGA 1851 / 1700 / 1200 / 1151 / 1150 / 1155 / 1156 sockets |                                               |
|                        | AMD® AM5 / AM4 sockets                                            |                                               |
| Dimensions (L x W x H) |                                                                   | 102 x 85 x 136 mm / 4.0 x 3.2 x 5.3 inch      |
| Heat Sink Material     |                                                                   | 4 Heat Pipes / Direct Contact / Aluminum Fins |
| Fan                    | Dimensions (L x W x H)                                            | 92 x 92 x 25.4 mm (3.6 x 3.6 x 1 in.)         |
|                        | Quantity                                                          | 1 PCS                                         |
|                        | Speed                                                             | 650 ~ 2500 RPM (PWM) ± 10%                    |
|                        | Airflow                                                           | 76.2 m³/h(45.14 CFM)                          |
|                        | Noise Level                                                       | 30.04 dB(A)                                   |
|                        | Pressure                                                          | 3.25 mmH₂O (Max)                              |
|                        | MTTF                                                              | > 160,000 hours                               |
|                        | Power Connector                                                   | 4-Pin (PWM)                                   |
|                        | Rated Voltage                                                     | 12 VDC                                        |
|                        | Rated Current                                                     | 0.14 A                                        |
|                        | Safety Current                                                    | 0.18 A                                        |
|                        | Power Consumption                                                 | 1.68 W                                        |
| Warranty               |                                                                   | 2 years                                       |

## PACKING INFORMATION

|                                  |                       |
|----------------------------------|-----------------------|
| EAN Code                         | 4719512154656         |
| UPC Code                         | 884102126970          |
| Net weight                       | 0.506 kg              |
| Gross weight                     | 0.69 kg               |
| Package dimension<br>(L x W x H) | 10.9 x 13.3 x 16.2 cm |
| Carton dimension<br>(L x W x H)  | 56.5 x 28.6 x 19.6 cm |
| Unit / Pallet                    | 10                    |

| Cont. | W/ Pallet | Carton / Pallet | W/O Pallet |
|-------|-----------|-----------------|------------|
| 20'   | 6600      | 60              | N/A        |
| 40'   | 13200     | 60              | N/A        |
| 40 HQ | 14520     | 66              | N/A        |