



Power your play with the curved G-Master GCB2784HSU-B1 featuring 240Hz and 0.7ms response time

Experience absolute speed with a panoramic edge.

In high-stakes gaming, the slightest delay or motion blur can break your concentration and cost you the win. The [G-Master GCB2784HSU-B1](#) eliminates these barriers, pairing a satisfying 240Hz refresh rate with a 0.7ms MPRT response time for unparalleled motion clarity. Its 1500R curved VA panel delivers sharp FHD resolution, optimized for high-frame-rate performance, while pulling you deeper into the world and offering a superior static contrast ratio for the black depth. Supported by Adaptive Sync, this monitor delivers a seamless, high-velocity experience that ensures you see every movement first and react with perfect precision.

Available also with fixed stand : [G-Master GC2781HSU-B1 \(1920x1080\)](#) and [G-Master GC2784HSU-B1 \(1920x1080\)](#).



CURVED DESIGN 1500R

The 1500R curvature of the screen guarantees a realistic and comfortable viewing experience allowing you to really immerse yourself in the game.



FreeSync™ Premium Technology

This monitor guarantees low input latency and low framerate compensation putting an end to any tearing or stuttering issues at virtually any framerate.

01 DISPLAY CHARACTERISTICS

Design	curved
Diagonal	27", 68,6cm
Panel	VA
Curved	1500R
Native resolution	1920 x 1080 @240Hz
Aspect ratio	16:9
Panel brightness	350 cd/m ²
Static contrast	4000:1
Advanced contrast	80M:1
Response time (MPRT)	0.7ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mIn 8bit (sRGB: 99%; NTSC: 72%)
Horizontal Sync	30 - 300kHz
Viewable area W x H	597.9 x 336.3mm
Pixel pitch	0.311mm
Colour	black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (ver. 2.1 TMDS) DisplayPort x1 (v. 1.4)
USB HUB	x2 (v. 2.0; 5V, 500mA)

03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	FreeSync Premium - 1920 x 1080 @48-240Hz
HDR	HDR10
OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Control buttons	Power Indicator, Joystick: Power / Menu (Center), Up / Signal Select, Down, Left / i-Style Colour / Night Mode / Blue Light Reducer, Right / Volume
User controls	picture adjust (contrast, brightness, OD, HDR, FreeSync Premium, ACR, Night Mode, Blue Light Reducer, Motion Blur Reduction, Gamma), input select, audio settings (volume, mute), store user settings (user modes), colour settings (6-axis, colour temperature, user preset, black tuner), image adjust (i-Style Colour, x-res technology, sharpness, HDMI range, direct drive mode, video mode adjust), language, setup menu (OSD horizontal position, OSD vertical position, OSD time, opening logo, power LED, DDC/CI control, USB charge, PIP/PBP), display information, reset
Speakers	2 x 2W

04 MECHANICAL

Display position adjustments	height, pivot (rotation), swivel, tilt
Height adjustment	150mm
Rotation (PIVOT function)	90°
Swivel stand	45°; %3° left; %3° right
Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm

Cable management system

yes

05 ACCESSORIES INCLUDED

Cables

power (1.85m), USB (1.5m), HDMI (1.85m)

Other

quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit

internal

Power supply

AC 100 - 240V, 50/60Hz

Power usage

21W default, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations

CB, CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA

Energy efficiency class (Regulation (EU) 2017/1369)

E

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D

610,5 x 466,5 x 192,5mm

Box dimensions W x H x D

1150 x 1761 x 700mm

Weight (without box)

4kg

Weight (with box)

6,54kg

EAN code

4948570127566

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED