

Product datasheet

Specifications

NetBotz Rack 250A

NBRK0250A



Overview

Presentation	NetBotz Rack Monitor 250 with embedded NMC3
Lead time	Usually in Stock

Main

Number of rack unit	1U
Communication port protocol	HTTPS HTTP SNMP SNMP v3 Modbus
Provided equipment	Installation guide Rack mounting brackets Temperature/humidity sensor Installation gasket

General

Universal sensor supported	0-5V Door contact Dry contact Fluid spot leak Humidity Temperature Smoke
Number of universal sensor ports	6
Number of sensor pods supported	6

Physical

Height	4.4 cm
Width	43.2 mm
Depth	5.9 cm
Net weight	1.27 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Vertical

Environmental

Ambient air temperature for operation	0...45 °C
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...65 °C
Storage altitude	0.00...15240.00 m

Communications & Management

Communication network type	RJ45 10/100 Base-T
----------------------------	--------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.6 cm
Package 1 Width	22.6 cm
Package 1 Length	45.7 cm
Package 1 Weight	2.95 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)