

AXIS Fixed Box IR Illuminator Kit A

Power-efficient IR for surveillance at night

This optional IR kit accessory is designed to fit outdoor AXIS P13 Box Cameras and selected AXIS Q16 Box Cameras. It enables cost-efficient surveillance in pitch darkness and includes power-efficient, long-life 850 nm IR LEDs with a range of reach of 50 m (164 ft) or more depending on the scene. This IP66- and IK10-rated IR kit can easily be attached to and powered by the camera. It comes pre-mounted on AXIS P1377-LE and AXIS P1378-LE.

- > IR range up to 50 m (164 ft)
- > Robust with IK10 rating
- > Easy installation
- > Powered by the camera



AXIS Fixed Box IR Illuminator Kit A

Supported products	AXIS P1375-E Network Camera AXIS P1377-LE Network Camera AXIS P1378-LE Network Camera AXIS Q1656-BE Box Camera AXIS Q1656-BLE Box Camera AXIS Q1656-LE Box Camera	IEC/EN/UL 60598-1, IEC/EN/UL 60950-22, IS 13252, EN 62471 Environment IEC/EN 60529 IP66/IP67, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 62262 IK10
Type	OptimizedIR with power-efficient, long-life 850 nm IR LEDs	Operating conditions
Angle	120°	40 °C to 60 °C (-40 °F to 140 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Humidity 10–100% RH (condensing)
Distance	Range 50 m (164 ft) or more, depending on the scene	Storage conditions
Power	5.3 V, typical 8 W, max 10 W	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Environment	Outdoor	Dimensions
Casing	Aluminum and polycarbonate (window)	100 x 34 x 80 mm (3.9 x 1.3 x 3.1 in)
Approvals	EMC EN 50121-4, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), IEC 62236-4, KCC KN32 Class A, KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety	Weight
		270 g (0.6 lb)
		Warranty
		3-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility