

Ernitec 0070-08316 security camera Bulb IP security camera Indoor & outdoor 2592 x 1944 pixels Wall

Brand : Ernitec

Product code: 0070-08316

Product name : 0070-08316

- 2592x1944 @ 25/30fps (5MP)
 - 1/2.8" progressive scan CMOS
 - Min. illumination Color: 0.07 Lux @ (F1.6, AGC ON) B/W: 0.007 Lux, 0 Lux (IR LED ON)
 - Support face, human and vehicle detection and capture
 - Intelligent Analysis: intrusion, single line crossing, double line crossing, loitering, wrong way, illegal parking, people counting
 - Auto tracking and perimeter protection based on deep learning
 - Power Supply AC24V/DC36V/PoE+ (IEEE 802.3at)
 - IP66, TVS4000V. Operating temp: -40°C ~ 55°C
 - Wall Mount included.
 - 5 Year Warranty
- Jupiter Pro 5MP PTZ Camera with 30x Optical Zoom & IR 150m, PoE+, IP66 - NDAA



Ernitec 0070-08316 security camera Bulb IP security camera Indoor & outdoor 2592 x 1944 pixels Wall:

Jupiter PX-815IR

Performance		Video	
Type *	IP security camera	Frame rate	30 fps
Placement supported *	Indoor & outdoor	Noise reduction technology	3D noise reduction
Connectivity technology *	Wired	Image quality adjustment	Brightness, Contrast, Saturation, Sharpness
PTZ control	✓	Privacy masking	✓
PTZ modes	Preset point	Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
PTZ status display	✓	Bit rate	100 kbps - 12 Mbps
Auto-tracking	✓	Back Light Compensation (BLC)	✓
Preset points	✓	Highlight Compensation (HLC)	✓
Wide Dynamic Range (WDR)	✓	Region of Interest (ROI) encoding	✓
Day/night mode	✓	Smart IR	✓
Alarm input/output	✓	Audio	
Number of languages	10	Audio input channels	1.0 channels
Languages support	Multi	Audio output channels	1.0 channels
Design		Audio formats supported	G.711, PCM
Form factor *	Bulb	Signal-to-Noise Ratio (SNR)	55 dB
Mounting type *	Wall	Network	
Product colour *	Black, White	Ethernet LAN *	✓
Housing material	Metal	Ethernet interface type	Fast Ethernet
Protection features	Waterproof	Supported network protocols IPv4, IPv6, TCP / IP, HTTP, HTTPS, UPnP, RTSP / RTP / RTCP, IGMP / Multicast, SMTP, DHCP, NTP, DNS, DDNS, QoS, SNMP, 802.1X, UDP, ICMP, ARP, TLS	
International Protection (IP) code	IP66		
Fog proof	✓		
Camera		Wi-Fi *	✗
Camera pan control	✓	Bluetooth *	✗
Camera tilt control	✓	Number of users	10 user(s)
Minimum illumination	0 lx	Streaming method	Unicast
Angle of rotation	360°	Storage	
Lens viewing angle, horizontal	56.62 - 2.48°	Built-in HDD *	✗
Lens viewing angle, vertical	42.76 - 1.91°	Card reader integrated	✓
Tilt angle range	0 - 90°	Maximum memory card size	256 GB
Tilt preset speed	90 °/sec		
Tilt manual speed	0.1 - 90 °/sec		
Pan range	0 - 360°		

Camera		Ports & interfaces	
Pan preset speed	180 °/sec	Ethernet LAN (RJ-45) ports	1
Pan manual speed	0.1 - 180 °/sec	Security	
White balance	Auto, Manual	Alarm input channels	2
Preset programs quantity	400	Alarm output channels	2
Camera shutter speed	1/5 - 1/20000 s	Video motion detection	✓
Image sensor		Intelligent Video Surveillance (IVS) system features	Crossing line, Human detection, Intrusion, People counting, Vehicle detection
Number of sensors	1	Mirror	✓
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Management features	
Progressive scan	✓	Web-based management	✓
Sensor type *	CMOS	Power	
Lens system		Power source type *	AC, DC, PoE
Zoom capability	✓	AC input voltage	24 V
Optical zoom	30x	Power consumption (typical)	30 W
Digital zoom	16x	DC output voltage	36
Number of lenses *	1	Operational conditions	
Focal length range	5.3 - 159 mm	Operating temperature (T-T)	-40 - 55 °C
Auto focus	✓	Operating relative humidity (H-H)	0 - 90%
Focus	Motorized/Manual	Weight & dimensions	
Maximum aperture number	4.3	Height	292.6 mm
Minimum aperture number	1.6	Diameter	17.3 cm
Night vision		Weight	3.5 kg
Night vision *	✓	Packaging data	
Night vision distance	150 m	Package weight	5 kg
LED type	IR	Sustainability	
Video		Sustainability compliance	✓
Maximum resolution *	2592 x 1944 pixels	Compliance certificates	CE, Federal Communications Commission (FCC)
Total megapixels *	5 MP	Packaging content	
		Number of cameras *	1
		Technical details	
		Number of video streams	3



5715063068137

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.