

## Vertiv Liebert GXE3-2000IRT2UXL uninterruptible power supply (UPS) Double-conversion (Online) 2 kVA 1800 W 8 AC outlet(s)

**Brand :** Vertiv

**Product family:** Liebert

**Product code:**  
GXE3-2000IRT2UXL

**Product name :**  
GXE3-2000IRT2UXL

- Reliable online double-conversion topology
  - High output power factor (0.9) to protect more loads
  - Hot-swappable user replaceable internal batteries without load shutdown
  - Remote management and server shutdown with the optional network management card
  - Fast recharge time (<4hrs @90%) and scalable runtime capabilities in rack/tower models
- Liebert GXE UPS 2000VA/1800W 230V Online Double Conversion Rack/Tower | Lead Acid VRLA Battery | Optional battery cabinets (GXE3-2000IRT2UXL)
- Vertiv Liebert GXE3-2000IRT2UXL. UPS topology: Double-conversion (Online), Output power capacity: 2 kVA, Output power: 1800 W. AC outlet types: C13 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 3.2 min, Typical backup time at half load: 9 min. Form factor: Rackmount/Tower, Product colour: Grey, Rack capacity: 2U. Compliance certificates: CB, CE, RCM, REACH, RoHS, UKCA, WEEE



| Features                            |                            | Battery                           |                                                  |
|-------------------------------------|----------------------------|-----------------------------------|--------------------------------------------------|
| UPS topology *                      | Double-conversion (Online) | Typical backup time at half load  | 9 min                                            |
| Output power capacity *             | 2 kVA                      | Battery life (max)                | 5 year(s)                                        |
| Output power *                      | 1800 W                     | Battery recharge time             | 4 h                                              |
| Waveform *                          | Pure sine                  | Design                            |                                                  |
| Input operation voltage (min) *     | 110 V                      | Form factor *                     | Rackmount/Tower                                  |
| Input operation voltage (max) *     | 290 V                      | Rack capacity                     | 2U                                               |
| Input frequency *                   | 40 - 70 Hz                 | Product colour *                  | Grey                                             |
| Output operation voltage (min)      | 220 V                      | Display type                      | LCD                                              |
| Output operation voltage (max)      | 240 V                      | Operational conditions            |                                                  |
| Surge energy rating                 | 600 J                      | Operating temperature (T-T)       | 0 - 40 °C                                        |
| Efficiency (On-line mode)           | 89%                        | Storage temperature (T-T)         | -20 - 50 °C                                      |
| Efficiency (ECO mode)               | 95%                        | Operating relative humidity (H-H) | 5 - 90%                                          |
| EMI/RFI noise filtering             | ✓                          | Operating altitude                | 0 - 2000 m                                       |
| Noise level                         | 53 dB                      | Certificates                      |                                                  |
| Ports & interfaces                  |                            | Compliance certificates           | CB, CE, RCM, REACH, RoHS, UKCA, WEEE             |
| AC outlet types                     | C13 coupler                | Packaging content                 |                                                  |
| AC outlets quantity                 | 8 AC outlet(s)             | Cables included                   | Input power cable, Output power cable, USB cable |
| USB port                            | ✓                          | Quick installation guide          | ✓                                                |
| Emergency Power Off (EPO) connector | ✓                          | Sustainability                    |                                                  |
| Battery                             |                            | Sustainability compliance         | ✓                                                |
| Battery technology                  | Sealed Lead Acid (VRLA)    | Weight & dimensions               |                                                  |
| Number of batteries supported       | 4                          | Width                             | 438 mm                                           |
| Typical backup time at full load    | 3.2 min                    | Depth                             | 430 mm                                           |
|                                     |                            | Height                            | 86 mm                                            |

| Weight & dimensions |         |
|---------------------|---------|
| Weight              | 22.7 kg |
| Packaging data      |         |
| Package width       | 560 mm  |
| Package depth       | 600 mm  |
| Package height      | 235 mm  |
| Package weight      | 24.8 kg |



0767041034417



767041034417

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.