



# Lindy 7.5m Cat.5e U/UTP Network Cable, Grey

**Brand :** Lindy **Product code:** 48366

**Product name :** 7.5m Cat.5e U/UTP Network Cable, Grey

7.5m Cat.5e U/UTP Network Cable, Grey


Lindy 7.5m Cat.5e U/UTP Network Cable, Grey:

Cat.5e U/UTP PVC network cable with support for bandwidth up to 100MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.5e cable, designed for operating frequencies up to 100MHz. The unshielded version (U/UTP) is designed in its electrophysical parameters (NExT, FExT etc.) in such a way that it can be used for Gigabit Ethernet despite the lack of shielding. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m, 40m, 50m, 60m, 70m, 80m, 90m, 100m.



| Features                   |                          | Operational conditions         |                                            |
|----------------------------|--------------------------|--------------------------------|--------------------------------------------|
| Product colour *           | Grey                     | Operating temperature (T-T)    | -10 - 60 °C                                |
| Cable length *             | 7.5 m                    | Storage temperature (T-T)      | -20 - 75 °C                                |
| Cable standard *           | Cat5e                    | Sustainability                 |                                            |
| Cable shielding *          | U/UTP (UTP)              | Doesn't contain                | Halogen                                    |
| Connector 1 *              | RJ-45                    | Certificates                   |                                            |
| Connector 2 *              | RJ-45                    | Certification                  | RoHS, REACH, UL, California Proposition 65 |
| Connector 1 gender *       | Male                     | Weight & dimensions            |                                            |
| Connector 2 gender *       | Male                     | Outer diameter                 | 4.8 mm                                     |
| Connector contacts plating | Gold                     | Connector 1 dimensions (WxDxH) | 11.6 x 22.8 x 8.3 mm                       |
| Jacket material            | Polyvinyl chloride (PVC) | Connector 2 dimensions (WxDxH) | 11.6 x 22.8 x 8.3 mm                       |
| Conductor type             | Stranded                 | Packaging content              |                                            |
| Conductor material         | Copper                   | Quantity per pack              | 1 pc(s)                                    |
| Cable type                 | Straight-through cable   | Packaging data                 |                                            |
| Cabling technology         | 10/100/1000Base-T(X)     | Package type                   | Polybag                                    |
| AWG wire size              | 26                       | Logistics data                 |                                            |
| Data transfer rate         | 1000 Mbit/s              | Harmonized System (HS) code    | 84733080                                   |
| Frequency                  | 100 MHz                  |                                |                                            |
| Bend radius (min)          | 5.7 cm                   |                                |                                            |
| Molded cable boot          | ✓                        |                                |                                            |



4002888483667

### **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.