



Dahua Technology DH-XVR5416L-4KL-I3 digital video recorder (DVR) Black



Brand : Dahua Technology

Product code: DH-XVR5416L-4KL-I3

Product name : DH-XVR5416L-4KL-I3

- H.265+/H.265 dual-stream video compression
 - Supports 16-channel AI-Coding
 - Supports HDCVI/AHD/TVI/CVBS/IP video inputs
 - Max 32 channels IP camera inputs, each channel up to 12MP; Max 128 Mbps incoming bandwidth
 - Up to 8 channels video stream (analog channel) perimeter protection
 - Up to 16 channels video stream (analog channel) SMD plus
 - Up to 2 channels video stream (analog channel) human face recognition
 - IoT & POS functionalities
- 2 channels, 16 BNC ports, 32 kbps-6144 kbps, 8 kHz, 16 bit, RJ-45, 2 HDMI, 1 VGA, 1 TV, 4.7 kg

Performance		Network	
Maximum video resolution	3840 x 2160 pixels	Ethernet LAN	✓
Video compression formats	H.264, H.264+, H.265, H.265+	Ethernet interface type	Gigabit Ethernet
Audio formats supported	G.711 A-law, G.711 µ-law, PCM	Ethernet LAN (RJ-45) ports	1
Video loss detection	✓	Supported network protocols	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P
Video motion detection	✓		
Playback resolutions supported	3840 x 2160, 1920 x 1080, 1280 x 1024, 1280 x 720	Hard drive	
Product colour *	Black	Number of HDDs supported	4
Playback modes	Event, General, Instant, Smart, Tag	HDD interface	SATA III
Audio output channels	1.0 channels	Maximum HDD capacity	16 TB
USB connectivity	✓	Processor	
Bit rate	6144 Kbit/s	Built-in processor	✓
Rack capacity	1.5U	Power	
Certification	CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2, EN 61000-3-3, EN 55032, EN 50130, EN 55024 FCC: Part 15 Subpart B	Power supply type	AC
Ports & interfaces		AC input voltage	100 - 240 V
Alarm input channels	16	Power consumption (typical)	20 W
Alarm output channels	6	Weight & dimensions	
BNC input ports	16	Width	440 mm
HDMI ports quantity	1	Depth	420.2 mm
VGA (D-Sub) output ports	1	Height	76 mm
USB 2.0 ports quantity	1	Weight	4.7 kg
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Packaging data	
RS-485 ports	1	Package width	529 mm
eSATA ports quantity	1	Package depth	499 mm
RS-232 ports	1	Package height	211 mm
		Package weight	6.9 kg
		Operational conditions	
		Operating temperature (T-T)	-10 - 55 °C
		Operating relative humidity (H-H)	10 - 90%

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.