

NEOZED FUSE LINK 400V GL, SIZE D03, 80A



Model	
Product brand name	SETRON
Product designation	NEOZED fuse link
Product variations	Pack of 10
Design of the fuse link	NEOZED fuse link
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	D03
Operating class of the fuse link	gG
Supply voltage	
• at AC / rated value	400 V
• at DC	250 V
Protection class IP	IP20, with connected conductors
Switching capacity current / acc. to IEC 60947-2 / rated value	50 kA
Dissipation	
Power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	5.4 W

• maximum	5.4 W
Current / at AC / rated value	80 A

Main circuit	
Operating voltage / rated value	400 V
Operating current / rated value	80 A

Appearance	
Color coding of the fuse link	Blue
Maximum short-circuit current breaking capacity (Icu) / at AC / rated value	50 kA
Mounting position	Any, preferably vertical
Net weight	36 g
Environmental category	Up to 45°C at 95 % rel. humidity

Certificates	
• Reference identifier / acc. to DIN EN 61346-2	F
• Reference identifier / acc. to DIN EN 81346-2	F

General Product Approval	Declaration of Conformity	Test Certificates			other
 VDE	 EG-Konf.	Type Test Certificates/Test Report	Special Test Certificate	Miscellaneous	Environmental Confirmations

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE2280>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SE2280>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2280

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

