



DeepCool PL800D power supply unit 800 W 20+4 pin ATX ATX
Black

Brand : DeepCool

Product code: R-PL800D-FC0B-EU-V2

Product name : PL800D

800W, ATX12V V3.0, APFC, 120 mm, 20+4 Pin, 2x 4+4 Pin, 3x PCI-E 6+2 Pin, 6x SATA, 12VHPWR, 150 × 140 × 86 mm, Black, EU
DeepCool PL800D. Total power: 800 W, AC input voltage: 100 - 240 V, AC input frequency: 50/60 Hz.
Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 55 cm, SATA power cable length: 550,450,650 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm.
Compliance certificates: RoHS, WEEE, Certification: CE/FCC/CCC/RCM/EAC/CAN ICES-003(B)/NMB-003(B) /TUV-RH

Power		Ports & interfaces	
Total power *	800 W	ATX power connector (20+4 pin)	✓
AC input voltage *	100 - 240 V	Cabling type	Non-Modular
AC input frequency	50/60 Hz	Performance	
Input current	9 - 4.5 A	80 PLUS certification *	80 PLUS Bronze
Power Factor Correction (PFC) type	Active	Purpose *	PC
Combined power (+3.3V)	100 W	Power supply unit (PSU) form factor *	ATX
Combined power (+12V)	648 W	ATX version	3.0
Combined power (+5V)	100 W	Bearing technology	HYB
Combined power (-12V)	3.6 W	Mean time between failures (MTBF)	100000 h
Combined power (+5Vsb)	15 W	Design	
Max output current (+3.3V)	20 A	Product colour	Black
Max output current (+12V)	54 A	Cooling type	Active
Max output current (+5V)	20 A	Fan diameter	12 cm
Max output current (-12V)	0.3 A	Number of fans	1 fan(s)
Max output current (+5Vsb)	3 A	Fan location	Top
Hold time	16 ms	On/off switch	✓
Efficiency	85%	Operational conditions	
Power Good signal delay range	100 - 150 ms	Operating temperature (T-T)	0 - 40 °C
Power protection features	No load operation, Over current, Over power, Over voltage, Overheating, Surge & inrush protection (SIP), Surge protection, Under voltage	Certificates	
Ports & interfaces		Compliance certificates	RoHS, WEEE
Motherboard power connector *	20+4 pin ATX	Certification	CE/FCC/CCC/RCM/EAC/CAN ICES-003(B)/NMB-003(B) /TUV-RH
Motherboard power cable length	55 cm	Weight & dimensions	
Number of SATA power connectors	6	Width	150 mm
SATA power cable length	550,450,650 mm	Depth	140 mm
Peripheral (Molex) power connectors (4-pin) *	2	Height	86 mm
PCI Express power connectors (6+2 pin)	3	Packaging data	
PCI Express power connectors (16-pin)	1	Package type	Box
CPU power connector (4+4 pin)	✓	Technical details	
		Sustainability compliance	✓
		Sustainability certificates	ErP, Triman
		Logistics data	
		Country of origin	China



6933412721529

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-MAY-2026. Prints or copies of Information are only valid on the printed Publication date