Canon

Canon i-SENSYS MF553DW Laser A4 1200 x 1200 DPI 43 ppm Wi-Fi

Brand : Canon **Product family:** i-SENSYS **Product code:** 5160C010

Product name : MF553DW

A4, 43ppm, 1200 x 1200 dpi, Secure PIN print, LCD Colour Touch Screen, USB 2.0, LAN, WLAN, 220-240V Canon i-SENSYS MF553DW. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying, Maximum copy resolution: 600 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Faxing: Mono faxing. Duplex functions: Copy, Print, Scan. Maximum ISO A-series paper size: A4. Wi-Fi. Direct printing. Product colour: Black, White

Printing	
Print technology *	Laser
Printing *	Mono printing
Duplex printing *	✔
Maximum resolution *	1200 x 1200 DPI
Print speed (black, normal quality, A4/US Letter) *	43 ppm
Warm-up time	14 s
Time to first page (black, normal)	5.7 s
Secure printing	✔

Copying	
Duplex copying *	✔
Copying *	Mono copying
Maximum copy resolution *	600 x 600 DPI
Maximum number of copies	999 copies
Copier resize	25 - 400%
N-in-1 copy function	✔
N-in-1 copy function (N=)	2, 4
ID-card copy function	✔

Scanning	
Duplex scanning *	✔
Scanning *	Colour scanning
Optical scanning resolution *	600 x 600 DPI
Scanner type *	ADF scanner
Scan to	Cloud, E-mail
Image formats supported	JPEG, TIFF
Document formats supported	PDF
Input colour depth	24 bit
Output colour depth	24 bit
Greyscale levels	256
Scan drivers	ICA, TWAIN, WIA

Fax	
Faxing *	Mono faxing
Fax resolution (black)	200 x 100 DPI
Modem speed	33.6 Kbit/s
Fax memory	512 pages
Speed dialling	✔

Features	
Recommended duty cycle	2000 - 75000 pages per month
Maximum duty cycle *	150000 pages per month
Duplex functions *	Copy, Print, Scan
Printing colours *	Black
Page description languages	PCL 5e, PCL 6, PostScript 3, UFRII

Paper handling	
ISO B-series sizes (B0...B9)	B5
Non-ISO print media sizes	Executive, Legal, Letter, Oficio, Statement
Envelopes sizes	C5, Com-10, DL, Monarch
Paper tray media weight	60 - 120 g/m²
Multi-Purpose Tray media weight	60 - 199 g/m²

Ports & interfaces	
Direct printing *	✔
USB port	✔
USB 2.0 ports quantity	1

Network	
Wi-Fi *	✔
Ethernet LAN *	✔
Cabling technology	10/100/1000Base-T(X)
Ethernet LAN data rates	10,100,1000 Mbit/s
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Security algorithms	64-bit WEP, 128-bit WEP, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPA2-TKIP

Performance	
Internal memory *	1024 MB
Built-in processor	✔
Processor frequency	800 MHz
Sound pressure level (printing)	54 dB
Sound pressure level (standby)	24 dB

Design	
Product colour *	Black, White
Market positioning *	Business
Built-in display *	✔
Display	LCD
Control type	Touch
Colour display	✔

Power	
Power consumption (max)	1430 W
Power consumption (printing)	590 W
Power consumption (standby)	13.6 W
Power consumption (sleep)	0.9 W
Energy Star Typical Electricity Consumption (TEC)	0.41 kWh/week
AC input voltage	220 - 240 V
AC input frequency	50 - 60 Hz

Features	
Printer fonts	PCL, PostScript
Input & output capacity	
Total number of input trays *	1
Total input capacity *	550 sheets
Total output capacity *	150 sheets
Multi-Purpose tray	✔
Multi-Purpose tray input capacity	100 sheets
Auto document feeder (ADF)	✔
Auto document feeder (ADF) input capacity	50 sheets
Maximum input capacity	2300 sheets
Paper handling	
Maximum ISO A-series paper size *	A4
Paper tray media types *	Envelopes, Heavy paper, Labels, Plain paper, Postcard, Recycled paper, Thin paper
ISO A-series sizes (A0...A9) *	A4, A5, A6

System requirements	
Windows operating systems supported	Windows 10, Windows 11, Windows 8.1
Mac operating systems supported	Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur
Linux operating systems supported	✔
Server operating systems supported	Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Operational conditions	
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	10 - 30 °C
Weight & dimensions	
Width	494 mm
Depth	464 mm
Height	452 mm
Weight	19.8 kg
Logistics data	
Harmonized System (HS) code	84433100

4549292186444

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2026. Prints or copies of Information are only valid on the printed Publication date